


Seal — NBR O-ring

CE RoHS



Material: NBR
 Performance: RoHS compliant
 Working temperature: -20°C to 80°C
 Application: Available for kinds of plastic/metal cable glands, hose connectors, blind plugs, etc.




P/N	Thread Size	ID mm	OD mm	T mm	Reference No.	
OR.NBR.10BK	M12,PG7	10	13	1.5	9 00 056 4100 2	100
OR.NBR.13BK	M16,PG9	13	16.6	1.8	9 00 056 4130 2	100
OR.NBR.14BK	M18	14	17.6	1.8	9 00 056 4140 2	100
OR.NBR.16BK	PG11	16	19.6	1.8	9 00 056 4160 2	100
OR.NBR.17BK	M20,PG13.5	17	20.8	1.9	9 00 056 4170 2	100
OR.NBR.18BK	M22,PG16,M25	18	22	2	9 00 056 4180 2	100
OR.NBR.22BK	PG21	22	27	2.5	9 00 056 4220 2	100
OR.NBR.29BK	M32	29	33	2	9 00 056 4290 2	100
OR.NBR.33BK	M40,PG29	32.5	37.8	2.65	9 00 056 4330 2	50
OR.NBR.42BK	M50,PG36	42	47.3	2.65	9 00 056 4420 2	50
OR.NBR.48BK	PG42	47.5	52.7	2.6	9 00 056 4480 2	50
OR.NBR.53BK	M63,PG48	53	58	2.5	9 00 056 4530 2	50

Seal — Silicone Rubber O-ring

CE RoHS



Material: Silicone Rubber
 Performance: RoHS compliant
 Working temperature: -40°C to 80°C
 Application: Available for kinds of plastic/metal cable glands, hose connectors, blind plugs, etc.



P/N	Thread Size	ID mm	OD mm	T mm	Reference No.	
OR.SI.10BK	M12,PG7	10	13	1.5	9 00 057 4100 2	100
OR.SI.13BK	M16,PG9	13	16.6	1.8	9 00 057 4130 2	100
OR.SI.14BK	M18	14	17.6	1.8	9 00 057 4140 2	100
OR.SI.16BK	PG11	16	19.6	1.8	9 00 057 4160 2	100
OR.SI.17BK	M20,PG13.5	17	20.8	1.9	9 00 057 4170 2	100
OR.SI.18BK	M22,PG16,M25	18	22	2	9 00 057 4180 2	100
OR.SI.22BK	PG21	22	27	2.5	9 00 057 4220 2	100
OR.SI.29BK	M32	29	33	2	9 00 057 4290 2	100
OR.SI.33BK	M40,PG29	32.5	37.8	2.65	9 00 057 4330 2	50
OR.SI.42BK	M50,PG36	42	47.3	2.65	9 00 057 4420 2	50
OR.SI.48BK	PG42	47.5	52.7	2.6	9 00 057 4480 2	50
OR.SI.53BK	M63,PG48	53	58	2.5	9 00 057 4530 2	50

Seal — Flat NBR O-ring – Metric thread

CE RoHS




Material: NBR

Application: Available for kinds of hose connectors

Performance: Oil resistant, RoHS compliant

Working temperature: -40°C to 120°C




P/N	Thread Size	ID mm	OD mm	T mm	Reference No.	
FR.M12	M12	10.5	15	1.6	9 00 058 0120 2	100
FR.M16	M16	14.5	19	2	9 00 058 0160 2	100
FR.M18	M18	16.5	22	2	9 00 058 0180 2	100
FR.M20	M20	18.5	24	2	9 00 058 0200 2	100
FR.M25	M25	23.5	30	2	9 00 058 0250 2	100
FR.M32	M32	30.5	38	2.5	9 00 058 0320 2	100
FR.M40	M40	38.5	46	2.5	9 00 058 0400 2	50
FR.M50	M50	48.5	56	2.5	9 00 058 0500 2	50
FR.M63	M63	61.5	67	2.5	9 00 058 0630 2	50

Seal — Flat NBR O-ring – PG thread

CE RoHS




Material: NBR
 Application: Available for kinds of hose connectors
 Performance: Oil resistant, RoHS compliant
 Working temperature: -40°C to 120°C



P/N	Thread Size	ID mm	OD mm	T mm	Reference No.	
FR.PG7	PG7	11.5	15	2	9 00 058 1070 2	100
FR.PG9	PG9	14	19	2	9 00 058 1090 2	100
FR.PG11	PG11	17.5	22	2	9 00 058 1110 2	100
FR.PG13.5	PG13.5	19	24	2	9 00 058 1130 2	100
FR.PG16	PG16	21	27	2	9 00 058 1160 2	100
FR.PG21	PG21	27	33	2.5	9 00 058 1210 2	100
FR.PG29	PG29	35.5	42	2.5	9 00 058 1290 2	50
FR.PG36	PG36	45.5	52	2.5	9 00 058 1360 2	50
FR.PG42	PG42	58	65	2.5	9 00 058 1420 2	50

CCS — Conduit clip with Integral Lid

CE RoHS




Material: PA

Working temperature: -40°C to 100°C, or instantaneous up to 120°C;


Color: Black(RAL9005), Grey(RAL7037)

Fire resistance: UL94-V2



P/N	Thread Size	B mm	H mm	T mm	Screw Size	A mm	Reference No. (Grey)	Reference No. (Black)	
CCS.AD10(B/G)	AD10.0	30	23	12.5	M4	7.5	9 00 086 6100 1	9 00 086 6100 2	100
CCS.AD13(B/G)	AD13.0	30	23	12.5	M5	9	9 00 086 6130 1	9 00 086 6130 2	100
CCS.AD15.8(B/G)	AD15.8	30	23	12.5	M5	9	9 00 086 6160 1	9 00 086 6160 2	100
CCS.AD18.5(B/G)	AD18.5	35	30	15	M5	9	9 00 086 6190 1	9 00 086 6190 2	100
CCS.AD21.2(B/G)	AD21.2	35	30	15	M6	11.5	9 00 086 6220 1	9 00 086 6220 2	50
CCS.AD28.5(B/G)	AD28.5	42	38	16	M6	11.5	9 00 086 6290 1	9 00 086 6290 2	50
CCS.AD34.5(B/G)	AD34.5	51	43	16	M6	11.5	9 00 086 6350 1	9 00 086 6350 2	25
CCS.AD42.5(B/G)	AD42.5	61	51	16	M6	11.5	9 00 086 6430 1	9 00 086 6430 2	25
CCS.AD54.5(B/G)	AD54.5	74	64	19	M6	11.5	9 00 086 6550 1	9 00 086 6550 2	20

CCS — Conduit clip without Integral Lid




Material: PA

Working temperature: -40°C to 100°C , or instantaneous up to 120°C ;

Color: Black(RAL9005), Grey(RAL7037)

Fire resistance: UL94-V2



P/N	Hose Size	B mm	H mm	T mm	Screw Size	A mm	Reference No. (Grey)	Reference No. (Black)	
CCSN.AD10(B/G)	AD10.0	30	23	12.5	M4	7.5	9 00 087 6100 1	9 00 087 6100 2	100
CCSN.AD13(B/G)	AD13.0	30	23	12.5	M5	9	9 00 087 6130 1	9 00 087 6130 2	100
CCSN.AD15.8(B/G)	AD15.8	30	23	12.5	M5	9	9 00 087 6160 1	9 00 087 6160 2	100
CCSN.AD18.5(B/G)	AD18.5	35	30	15	M5	9	9 00 087 6190 1	9 00 087 6190 2	100
CCSN.AD21.2(B/G)	AD21.2	35	30	15	M6	11.5	9 00 087 6220 1	9 00 087 6220 2	50
CCSN.AD25(B/G)	AD25.0	40	35	16	M6	11.5	9 00 087 6250 1	9 00 087 6250 2	50
CCSN.AD28.5(B/G)	AD28.5	42	38	16	M6	11.5	9 00 087 6290 1	9 00 087 6290 2	50
CCSN.AD34.5(B/G)	AD34.5	51	43	16	M6	11.5	9 00 087 6350 1	9 00 087 6350 2	25
CCSN.AD42.5(B/G)	AD42.5	61	51	16	M6	11.5	9 00 087 6430 1	9 00 087 6430 2	25
CCSN.AD54.5(B/G)	AD54.5	74	64	19	M6	11.5	9 00 087 6550 1	9 00 087 6550 2	20