


压接插针参数 Crimp contact

5A压接插针 5A Crimp contact

※接触直径: Ø1
Contact diameter: Ø1
※材料: 铜镀金
Material: Brass with gold plating
※接触电阻: 5mΩ
Contact resistance: 5mΩ



5A压接公插针 5A Male crimp contact

用于SF、SA、SP、SY、WP系列、WS/WF/WY16-28型产品
For SF, SA, SP, SY, WP, WS/WF/WY16-28

线规 Wire size	剥线长度 Stripping length	压接公插针 Male crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
0.20-0.52mm ² AWG 24-20	5.5mm	YJ1-17-0.52AU	CTW-0.14/4	RT-1.0





5A压接母插针 5A Female crimp contact

用于SF、SA、SP、SY、WP系列、WS/WF/WY16-28型产品
For SF, SA, SP, SY, WP, WS/WF/WY16-28

线规 Wire size	剥线长度 Stripping length	压接母插针 Female crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
0.20-0.52mm ² AWG 24-20	5.5mm	YK1-17-0.52AU	CTW-0.14/4	RT-1.0

10A压接插针 10A Crimp contact

※接触直径: Ø1.5
Contact diameter: Ø1.5
※材料: 铜镀金
Material: Brass with gold plating
※接触电阻: 2.5mΩ
Contact resistance: 2.5mΩ



10A压接公插针 10A Male crimp contact

用于SF、SA、SP、SY、WP系列、WS/WF/WY16-28型产品
For SF, SA, SP, SY, WP, WS/WF/WY16-28

线规 Wire size	剥线长度 Stripping length	压接公插针 Male crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
0.14-0.37mm ²	AWG 26-22	8mm	YJ1.5-21.4-0.37AU	CTW-0.14/4 RT-1.5
0.5mm ²	AWG 20	8mm	YJ1.5-21.4-0.5AU	CTW-0.14/4 RT-1.5
0.75-1.0mm ²	AWG 18	8mm	YJ1.5-21.4-1.0AU	CTW-0.14/4 RT-1.5
1.5mm ²	AWG 16	8mm	YJ1.5-21.4-1.5AU	CTW-0.14/4 RT-1.5
2.5mm ²	AWG 14	8mm	YJ1.5-21.4-2.5AU	CTW-0.14/4 RT-1.5

10A压接公插针 10A Male crimp contact

用于WS/WF/WY32-55型产品
For WS/WF/WY32-55

线规 Wire size	剥线长度 Stripping length	压接公插针 Male crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
0.14-0.37mm ²	AWG 26-22	8mm	YJ1.5-23.6-0.37AU	CTW-0.14/4 RT-1.5
0.5mm ²	AWG 20	8mm	YJ1.5-23.6-0.5AU	CTW-0.14/4 RT-1.5
0.75-1.0mm ²	AWG 18	8mm	YJ1.5-23.6-1.0AU	CTW-0.14/4 RT-1.5
1.5mm ²	AWG 16	8mm	YJ1.5-23.6-1.5AU	CTW-0.14/4 RT-1.5
2.5mm ²	AWG 14	8mm	YJ1.5-23.6-2.5AU	CTW-0.14/4 RT-1.5

10A压接母插针 10A Female crimp contact

用于SF、SA、SP、SY、WP系列、WS/WF/WY16-28型产品
For SF, SA, SP, SY, WP, WS/WF/WY16-28

线规 Wire size	剥线长度 Stripping length	压接母插针 Female crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
0.14-0.37mm ²	AWG 26-22	8mm	YK1.5-20.4-0.37AU	CTW-0.14/4 RT-1.5
0.5mm ²	AWG 20	8mm	YK1.5-20.4-0.5AU	CTW-0.14/4 RT-1.5
0.75-1.0mm ²	AWG 18	8mm	YK1.5-20.4-1.0AU	CTW-0.14/4 RT-1.5
1.5mm ²	AWG 16	8mm	YK1.5-20.4-1.5AU	CTW-0.14/4 RT-1.5
2.5mm ²	AWG 14	8mm	YK1.5-20.4-2.5AU	CTW-0.14/4 RT-1.5



10A压接母插针 10A Female crimp contact

用于WS/WF/WY32-55型产品
For WS/WF/WY32-55

线规 Wire size	剥线长度 Stripping length	压接母插针 Female crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
0.14-0.37mm ²	AWG 26-22	8mm	YK1.5-22.6-0.37AU	CTW-0.14/4 RT-1.5
0.5mm ²	AWG 20	8mm	YK1.5-22.6-0.5AU	CTW-0.14/4 RT-1.5
0.75-1.0mm ²	AWG 18	8mm	YK1.5-22.6-1.0AU	CTW-0.14/4 RT-1.5
1.5mm ²	AWG 16	8mm	YK1.5-22.6-1.5AU	CTW-0.14/4 RT-1.5
2.5mm ²	AWG 14	8mm	YK1.5-22.6-2.5AU	CTW-0.14/4 RT-1.5

25A压接插针 25A Crimp contact

※接触直径: Ø2.5
Contact diameter: Ø2.5
※材料: 铜镀金
Material: Brass with gold plating
※接触电阻: 1mΩ
Contact resistance: 1mΩ



25A压接公插针 25A Male crimp contact

用于SF、SA、SP、SY、WP系列、WS/WF/WY16-28型产品
For SF, SA, SP, SY, WP, WS/WF/WY16-28

线规 Wire size	剥线长度 Stripping length	压接公插针 Male crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n	
0.75-1.0mm ²	AWG 18	8mm	YJ2.5-21.4-1.0AU	CTW-0.14/4	RT-2.5
1.5mm ²	AWG 16	8mm	YJ2.5-21.4-1.5AU	CTW-0.14/4	RT-2.5
2.5mm ²	AWG 14	8mm	YJ2.5-21.4-2.5AU	CTW-0.14/4	RT-2.5
4.0mm ²	AWG 12	8mm	YJ2.5-21.4-4.0AU	CTW-0.14/4	RT-2.5

25A压接公插针 25A Male crimp contact

用于WS/WF/WY32-55型产品
For WS/WF/WY32-55

线规 Wire size	剥线长度 Stripping length	压接公插针 Male crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n	
0.75-1.0mm ²	AWG 18	8mm	YJ2.5-23.6-1.0AU	CTW-0.14/4	RT-2.5
1.5mm ²	AWG 16	8mm	YJ2.5-23.6-1.5AU	CTW-0.14/4	RT-2.5
2.5mm ²	AWG 14	8mm	YJ2.5-23.6-2.5AU	CTW-0.14/4	RT-2.5
4.0mm ²	AWG 12	8mm	YJ2.5-23.6-4.0AU	CTW-0.14/4	RT-2.5

压接插针系列 Crimp contact

25A压接插套 25A Crimp contact

※接触直径: Ø2.5


Contact diameter: Ø2.5

※材料: 铜镀金

Material: Brass with gold plating

※接触电阻: 1mΩ

Contact resistance: 1mΩ



50A压接插针 50A Crimp contact

※接触直径: Ø3.5





Contact diameter: Ø3.5

※材料: 铜镀金

Material: copper

※接触电阻: 0.5mΩ

Contact resistance: 0.5mΩ



25A压接母插针 25A Female crimp contact

用于SF、SA、SP、SY、WP系列、WS/WF/WY16-28型产品
For SF, SA, SP, SY, WP, WS/WF/WY16-28

线规 Wire size	剥线长度 Stripping length	压接母插针 Female crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n	
0.75-1.0mm ²	AWG 18	8mm	YK2.5-20-1.0AU	CTW-0.14/4	RT-2.5
1.5mm ²	AWG 16	8mm	YK2.5-20-1.5AU	CTW-0.14/4	RT-2.5
2.5mm ²	AWG 14	8mm	YK2.5-20-2.5AU	CTW-0.14/4	RT-2.5
4.0mm ²	AWG 12	8mm	YK2.5-20-4.0AU	CTW-0.14/4	RT-2.5

25A压接母插针 25A Female crimp contact

用于WS/WF/WY32-55型产品
For WS/WF/WY32-55

线规 Wire size	剥线长度 Stripping length	压接母插针 Female crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n	
0.75-1.0mm ²	AWG 18	8mm	YK2.5-22.2-1.0AU	CTW-0.14/4	RT-2.5
1.5mm ²	AWG 16	8mm	YK2.5-22.2-1.5AU	CTW-0.14/4	RT-2.5
2.5mm ²	AWG 14	8mm	YK2.5-22.2-2.5AU	CTW-0.14/4	RT-2.5
4.0mm ²	AWG 12	8mm	YK2.5-22.2-4.0AU	CTW-0.14/4	RT-2.5

50A压接公插针 50A Male crimp contact

用于WS/WF/WY32-55型产品
For WS/WF/WY32-55

线规 Wire size		剥线长度 Stripping length	压接公插针 Male crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
1.5mm ²	AWG 16	10mm	YJ3.5-31-1.5AU	CT-0.14/4	RT-3.5
2.5mm ²	AWG 14	10mm	YJ3.5-31-2.5AU	CT-0.14/4	RT-3.5
4.0mm ²	AWG 12	10mm	YJ3.5-31-4.0AU	CT-0.14/4	RT-3.5
6.0mm ²	AWG 10	10mm	YJ3.5-31-6.0AU	CT-4/10	RT-3.5
10.0mm ²	AWG 7	10mm	YJ3.5-31-10.0AU	CT-4/10	RT-3.5

50A压接母插针 50A Female crimp contact

用于WS/WF/WY32-55型产品
For WS/WF/WY32-55

线规 Wire size	剥线长度 Stripping length	压接母插针 Female crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n
1.5mm²	AWG 16	10mm	YK3.5-27.6-1.5AU	CT-0.14/4 RT-3.5
2.5mm²	AWG 14	10mm	YK3.5-27.6-2.5AU	CT-0.14/4 RT-3.5
4.0mm²	AWG 12	10mm	YK3.5-27.6-4.0AU	CT-0.14/4 RT-3.5
6.0mm²	AWG 10	10mm	YK3.5-27.6-6.0AU	CT-4/10 RT-3.5
10.0mm²	AWG 7	10mm	YK3.5-27.6-10.0AU	CT-4/10 RT-3.5

50A压接公插针 50A Male crimp contact

用于SP29、SY29、SA28、WS/WF/WY28型2、3芯产品
For 2 & 3 pins of SP29, SY29, SA28, WS/WF/WY28

线规 Wire size	剥线长度 Stripping length	压接公插针 Male crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n	
4.0mm ²	AWG 12	10mm	YJ3.5-28-4.0AU	CT-4/10	RT-3.5
6.0mm ²	AWG 10	10mm	YJ3.5-28-6.0AU	CT-4/10	RT-3.5
10mm ²	AWG 7	10mm	YJ3.5-28-10.0AU	CT-4/10	RT-3.5
16mm ²	AWG 5	10mm	YJ3.5-28-16.0AU	YQK-70	RT-3.5

50A压接母插针 50A Female crimp contact


用于SP29、SY29、SA28、WS/WF/WY28型2、3芯产品
For 2 & 3 pins of SP29, SY29, SA28, WS/WF/WY28

线规 Wire size	剥线长度 Stripping length	压接母插针 Female crimp contact p/n	压接工具 Crimping tool p/n	退针工具 Removal tool p/n	
4.0mm ²	AWG 12	10mm	YK3.5-26.5-4.0AU	CT-4/10	RT-3.5
6.0mm ²	AWG 10	10mm	YK3.5-26.5-6.0AU	CT-4/10	RT-3.5
10mm ²	AWG 7	10mm	YK3.5-26.5-10.0AU	CT-4/10	RT-3.5
16mm ²	AWG 5	10mm	YK3.5-26.5-16.0AU	YQK-70	RT-3.5

压接插针参数 Crimp contact

50A压接插针 50A Crimp contact

※接触直径: Ø3.5
Contact diameter: Ø3.5
※材料: 铜镀银
Material: brass with silver plating
※接触电阻: 0.5mΩ
Contact resistance: 0.5mΩ




50A压接公插针 50A Male crimp contact			仅用于 WS/WF/WY16/SY17/SP17/SA16/SF16 型直式产品 For WS/WF/WY16/SY17/SP17/SA16/SF16
线规 Wire size	剥线长度 Stripping length	压接工具 Crimping tool p/n	
10.0mm ² AWG 7	10mm	YQK-70	

50A压接母插针 50A Female crimp contact			仅用于 WS/WF/WY16/SY17/SP17/SA16/SF16 型直式产品 For WS/WF/WY16/SY17/SP17/SA16/SF16
线规 Wire size	剥线长度 Stripping length	压接工具 Crimping tool p/n	
10.0mm ² AWG 7	10mm	YQK-70	

100A压接插针 100A Crimp contact

※接触直径: Ø5.5
Contact diameter: Ø5.5
※材料: 铜镀银
Material: brass with silver plating
※接触电阻: 0.3mΩ
Contact resistance: 0.3mΩ



100A压接公插针 100A Male crimp contact			仅用于 WS/WF/WY20/SP21/SY21/SA20/SF20/ WP20 型直式产品 For WS/WF/WY20/SP21/SY21/SA20/SF20/ WP20
线规 Wire size	剥线长度 Stripping length	压接工具 Crimping tool p/n	
25mm ² AWG 3	10mm	YQK-70	

100A压接母插针 100A Female crimp contact			仅用于 WS/WF/WY20/SP21/SY21/SA20/SF20/ WP20 型直式产品 For WS/WF/WY20/SP21/SY21/SA20/SF20/ WP20
线规 Wire size	剥线长度 Stripping length	压接工具 Crimping tool p/n	
25mm ² AWG 3	10mm	YQK-70	

压接钳 Crimp tool

用于插针的压接
For crimping the male / female contacts



型号 Part number	压线范围 Crimping wire range
YQK-70	4-70mm ² AWG 11-2/0

压接及退针工具 Crimp tool and Removal tool

压接工具 Crimp tool

用于插针的压接
For crimping the male / female contacts



型号 Part number	压线范围 Crimping wire range
CTW-0.14/4	0.14-4mm ² AWG 26-12

型号 Part number	压线范围 Crimping wire range
CT-4/10	4-10mm ² AWG 12-7

退针工具 Removal tool

用于公母插针退出
For taking out male / female contacts



型号 Part number	退针范围 Removal range
RT-1.0	5A压接插针 5A Male / Female crimp contact
RT-1.5	10A压接插针 10A Male / Female crimp contact
RT-2.5	25A压接插针 25A Male / Female crimp contact
RT-3.5	50A压接插针 50A Male / Female crimp contact

